LED Clock with Light & Wireless Qi Charger Model: AR1940

I. Function Buttons





II Functions

A. Power Connection

- 1. Plug the USB-A end of cable into the power adapter while plug Type-C end into the product.
- 2. The product will be ready and stand by after all indicators are on.
- B. Wireless Charging
- 1. Output: 10W
- 2. Indicator Display: Power connection successful blue light flashes once

Standby – light off

Charging – blue light on Charged – light off

FOD – blue light flashes continuously

C. Alarm Clock Functions

1. Four Buttons: Alarm. +. -. Light.

2. Time System Setting:

Double click Alarm button to setup 12-hour time system and 24-hour time system. AM and PM will display while 12-hour time system is set.

3. Time Setting:

1) Click Alarm button once to enter minute setting, adjust value with

·/-;

2) Click Alarm button once after minute setting, to enter hour setting, adjust value with +/-;

3) Click Alarm button a third time to finish time setting.

4. Alarm Setting:

1) Press "+" $\bar{\bf 3}$ seconds to activate or deactivate Alarm 1; Press "-" $\bar{\bf 3}$ seconds to activate or deactivate Alarm 2. Alarm indicator is on while Alarm is activated;

2) While activated, press Alarm button 3 seconds to enter alarm minute setting, adjust value with +/-;

3) Click Alarm button once after alarm minute setting, to enter alarm hour setting, adjust value with +/-;

4) Click Alarm button a third time to finish alarm time setting;

5) Alarm bell rings 3 minutes before automatic switch-off while no

any operation.

6) Touch any button to enter Sleepy Mode when bell rings. Bell will rings for 3 more times after 5 minutes. The indicator flashes and Alarm button is out of function during the Sleepy Mode. If time setting is needed, please long press "+" to stop alarm 1 or long press "-" to stop alarm 2. All buttons will function normally;

7) Time display brightness is automatically adjusted by 3 grades. Max brightness during 7am-5:59pm. Mid brightness during 6pm to 11:59pm. Min brightness during 12am-6:59am.

8) Time display brightness can also be adjusted manually to 3 grades (Min/Mid/Max). "+" and "-" can be used to adjust display brightness manually. The default grade is max brightness when power is connected. Single click "-" to dark the display one grade. The display brightness goes dark for the last grade and goes bright automatically 7am next day. All manual adjustment will be synchronized to automatic adjustment.

5. Night Light Setting:

1) Night light can be set into 9 color modes: white, RGB shade, red, yellow, light green, green, light blue, blue and pink;

2) Touch the Light button once to turn on the night light with white color. Another touch shall allow you to set another color in turn as specified in 5. 1). The last touch will turn off atmosphere light.

6. Eco-power function:

1) Button cell is only for time keeping.

All functions are out during power disconnection. Functions restored when power is connected.

). Note

 Attention: In order to function alarm, wireless charging, night light and USB output all together, power shall be connected by a QC2.0 or QC3.0 adapters. If connected by a 5V adapter, only wireless charging and alarm can work together.

2. Do not squeeze or collide.

3. Do not disassemble or put into the fire, water, to avoid short-circuit leakage.

4. Do not use wireless chargers in severe high temperature, humidity or corrosive environments to avoid leakage of damaged circuits.

5. Do not place too close to magnetic cards (ID cards, bank cards, etc.) with magnetic strips or chips to avoid magnetic card failure.

Keep more than 20cm between the implanted medical device (pacemaker, implantable cochlea, etc.) and the wireless charger to avoid potential disruption to medical devices.

7. Keep children from the product in case they play the wireless charger as a toy to avoid accidents.

8. Keep the wireless charger and receiver device away from water and other liquids.

9. To clean the charger, make sure the power supply is disconnected.

10. Usage temperature: 0-45°C.

11. Usage humidity: 20-85% (40°C)

* Pictures in this manual are all illustration. Final product is subject to fact.

* Inside package: alarm charger, charging cable, manual.

* power adapter is not included. Please purchase otherwise or use original phone adapter.

III. Specification

Input: 5V/2A, 9V/2A Output power: 10W (MAX)

Charging efficiency: 73% Charging distance: ≤8mm

Frequency: 110-205KHz Size: 145x116x73mm

IV. Applicable Devices

Products qualified with Qi standard.

Distributed by: Electus Distribution Pty. Ltd. 320 Victoria Rd, Rydalmere NSW 2116 Australia

www.electusdistribution.com.au

Made in China