


SPECIFICATION

DESCRIPTION: PLASTIC FRAME		SIZE :Φ 27mm	
NO	項目 ITEMS	規格 SPECIFICATIONS	測試條件 CONDITIONS
1	音圈阻抗 VOICE COIL IMPEDANCE	8Ω ±15%	
!	音圈尺寸 VOICE COIL SIZE	Φ5.8mm	
	音盆 CONE	MYLAR	FLAT CONE
"	動作 OPERATION	MUST BE NORMAL (without distortion)	AT 1000 Hz / rated power / sine wave
(異常音 SWEEP TEST	MUST BE NORMAL (without distortion)	At rated freq. range / rated power / sine wave
\$	共振頻率 RESONANT FREQ. (F0)	950Hz ± 20%	WITHOUT BAFFLE
,	特性靈敏度 OUTPUT S.P.L.	92 ±3 dB MEAN VALUE (at rated freq. range)	AT 0.1W / 0.1M MEASUREMENT (Average of : F0, 2K,3K & 4KHz)
-	頻率範圍 RATED FREQ RANGE	F0 Hz ~ 5K Hz	OUTPUT S.P.L. -10dB
B	額定功率 RATED POWER INPUT	0.1 WATTS	AT 0.89Vrms / 48hrs (pink noise)
10	最大功率 MAX POWER INPUT	0.25 WATTS	AT 1.41Vrms, pink noise (test 5s, stop 10s / 100 cycles)
11	失真率 DISTORTION	, 5% MAX	RATED POWER INPUT 1000 Hz
12	負荷試驗 LOAD TEST	AFTER TEST MEET ITEM 4&5	PINKNOISE 0.25W IN 48HOURS
13	耐熱試驗 HEAT TEST(STORAGE)	AFTER TEST MEET ITEM 4&5	55°C±2°C 20%--25% RH 48HOURS
14	耐濕試驗 HUMIDITY TEST(STORAGE)	AFTER TEST MEET ITEM 4&5	40°C±2°C 90%--95% RH 48HOURS
15	耐寒試驗 COLD TEST(STORAGE)	AFTER TEST MEET ITEM 4&5	-20°C±2°C 20%--25% RH 48HOURS
16	磁鐵 MAGNET	DAL Φ16× 7 mm × 5 mm WEIGHT OZ	
17	大概重量 APPROX. WEIGHT	NET : 7g ± 2g	
18	操作溫度 OPERATING TEMP. RANGE	-20°C±3°C TO 50°C±2°C	
19	備註 REMARKS		

Confirm to Directive 2002/95/EC on Restriction of Hazardous Substances (RoHS).

- 1) Cadmium in amounts not exceeding 100 ppm by weight of homogeneous material.
- !< Lead, Mercury, Hexavalent Chromium, Polybrominated Biphenyls(PBB) and Polybrominated Diphenyl Ethers(PBDE), in amounts not exceeding 1000 ppm by weight of homogeneous material.

Product outside view:



TEST CONDITION: $D=26.6\pm 0.3\text{mm}$

$H=9.0\pm 0.3\text{mm}$


Voltage = 0.89V

Distance = 0.1 M

Power = 0.1 W

Impedance = 8 Ω

Frequency Response Curve



Distributed by:
Electus Distribution Pty Ltd
46 Eastern Creek Dr,
Eastern Creek NSW 2766 Australia
1300 738 555 | electusdistribution.com.au

Made in China