


123456


# 说明书

## 技术要求

- 1、此页不印刷；
- 2、材质：105g双铜纸；
- 3、尺寸：成品尺寸，140\*210mm，装订款；
- 4、黑白印刷，印刷内容、字体、字体颜色（和文档一致）符合要求；
- 5、线框为裁剪线，不印刷；
- 6、制件符合RoHS要求。

03					物料编码	F042302	零件名称	说明书
02								
01					材料	比例	零件图号	EZGW41-05-08
序号	更改描述	更改文件号	签名	更改日期	105g双铜纸	1: 1	产品型号	EZGW
设计	张鸿飞	日期2022.12.29	会签	吴彩群	日期2022.12.29			
审核	冯志朗	日期2022.12.29	批准	樊钢强	日期2022.12.29			
						A版	佛山市艾凯电器有限公司	

123456



**41L / 51L / 61L  
Portable Dual Zone  
GH2073 / 2085 / 2087  
User Manual**

## FEATURES

- Dual zone - fridge / freezer operation.
- Optional removable 15.6AH or 7.8AH battery
- Solar charging interface
- Detachable lid - pivot point reversible.
- With cutting board
- With wheels and telescope handle
- DC power connections
- Powered by AC using the AC to DC power adapter
- High-efficiency DC compressor and conversion module
- Dual mode operation (Max & Economy)
- Digital temperature display with adjustable control
- 3 year warranty
- 3-stage low voltage battery protection
- APP control Via Bluetooth

## BOX CONTENTS

1 x Portable Dual Zone Fridge / Freezer  
1 x Mains to DC Power Adapter  
1 x 12 / 24V Car Cigarette Power Lead

## SPECIFICATIONS

Input Voltage:	12 / 24V DC, (To power from mains use the included 240V AC to 12V DC power adapter)
Average Power Consumption:	60W
Power Consumption:	0.25kw.h / 24hr
Rated Current for AC(Adaptor):	1.2A - 0.5A
Rated Current for DC:	5.0A (12V) / 2.5A (24V)
Temperature Range:	-20°C to + 20°C (with ambient temperature at 25°C)

Refrigerant:

R134a


Insulation:

100% CFC & HFC free PU  
Foam insulation


## SAFETY

- The installation of DC power sources in a boat must be handled by a qualified electrician
- Make sure to connect power to the suitable voltage socket
- No electrical devices are to be used inside the product
- The product can be powered on only after being unpacked and put on a flat level surface for over 6 hours
- Fridge operating angle:- The fridge can be operated indefinitely at up to 5 degrees, and can be operated at between 6 and 45 degrees for up to 30mins.
- Product must be well ventilated. Ensure there is a minimum of 200mm clearance at the back, and 100mm around the sides
- The product should be in a well-ventilated space, away from heat sources. Try to avoid direct exposure to sunlight
- Keep product stable
- When there is water inside the tank, do not turn the product upside down to empty. Dry the water, do not soak in water
- Do not put metal in the air inlet vent, outlet vent, or gap
- Do not connect with power except 12/24VDC, or the 240VAC to 12VDC power adapter (included)
- Do not soak the product in water or wash with water
- The product should not be repaired. If there is any issues please consult the place of purchase
- Turn off the product before cleaning to avoid electric shocks or other issues
- Keep product away from wet or humid places


## DIMENSIONS



**GH-2073**




**GH-2085**

















**GH-2087**

## OPERATION



\* **Note:** the right compartment is on the side where the compressor is.

- **Power supply:** connect to DC 12V/24V or AC 100~240V (using dedicated adapter) or solar (12~50V) power supply.
- **Display Screen Initialization:** when the fridge is powered on, the buzzer will make a long beep, and the display will be on for two seconds then enter the standby mode.
- **Power On/Off:** press  to switch ON, long press  for three seconds to switch OFF.
- **Temperature Setting:** under the running state, long press  and  at the same time for three seconds to switch ON/OFF the left compartment, long press  and  at the same time for three seconds to switch ON/OFF the right compartment, two compartments cannot be switched off at the same time. When both left and right compartments are set in running state, press  or  to enter left compartment temperature setting, press  to increase temperature, press  to decrease temperature, and press  to switch left/right compartment. The setting will be saved after stop operating for four seconds (Note: the temperature displayed is the current temperature of the compartments, it'll take a while to reach the set temperature.) Temperature setting range: -20~20°C (-4~68°F)




- **Cooling Mode:** under the running state, press  to switch MAX(fast cooling) and ECO(Energy saving Mode).(\*Factory setting is MAX.)
- **Battery Protection Mode:** under the running state, long press  for three seconds until screen flashes, then press  again to select protection mode H(High), M(Medium) and L(Low) (\*Factory setting is H.)

**Voltage Reference:**


INPUT MODE	DC 12V		DC 24V	
	CUT OUT	CUT IN	CUT OUT	CUT IN
L	8.5V	10.9V	21.3V	22.7V
M	10.1V	11.4V	22.3V	23.7V
H	11.1V	12.4V	24.3V	25.7V

\* the voltage is theoretical value, there may be a deviation in different sceneries.

\* H should be set when the product is connected to car power, and M or L should be set when it is connected to a portable battery or other back-up battery.

- **Temperature Unit Setting:** switch off the fridge, long press  for 3 seconds until displays E1, and switch to E5 by pressing  again, then press **+** or **-** to switch Celsius or Fahrenheit. (\*Factory setting is °C.)
- **Reset:** switch off the fridge, long press  for 3 seconds until displays E1, under E1 mode, long press **+** **-** at the same time for seconds to reset the settings.

## COMPONENTS




- |                           |                                   |
|---------------------------|-----------------------------------|
| 1. Cutting board          | 7. Sealing strip                  |
| 2. Left compartment       | 8. Right compartment              |
| 3. LED control panel      | 9. Handle                         |
| 4. Telescoping handle     | 10. Optional Rechargeable Battery |
| 5. Compressor compartment | 11. Wheel                         |
| 6. Lid latch              | 12. Power Socket                  |


## REVERSE LID OPENING DIRECTION

The lid opening direction can be changed according to actual needs, please follow the instructions below:


### Lid Disassembly:



Open the lid  
at a 90° angle




Take off the lid  
from one side




Take off the lid  
from the other side


### Lid Installation:



Reverse the  
lid opening  
direction




Align the lid shaft  
with the hole on one  
side and insert it



Fix the lid on  
the other side,  
installation finished

OPTIONAL BATTERY INFORMATION

Battery Model	Capacity	Rated Voltage	Charging Limited Voltage	Max Charging Current
GH-2051	7.8AH	11.1V	12.6V	4A
GH-2053	15.6AH	11.V	12.6V	4A



**WARNING:-** Do NOT connect the solar panel directly to the battery. This may result in fire.



Only use approved chargers with the fridge battery, incorrect chargers may result in fire, damage, a shortened battery life.

The fridge battery does NOT have an inbuilt solar charge controller and neither does the solar panel. Each solar and battery capable fridge has an inbuilt solar charge controller to safely charge any installed fridge battery, the solar panel must ONLY be plugged into the solar input on the fridge, and NEVER connect the solar panel directly to the battery, this may result in fire.

Do not disassemble, impact, squeeze, crush, or throw or misuse the fridge battery, do not dispose of in fire, any of which may result in short circuit and fire or explosion. If there is swelling and heating of the fridge battery do not continue to use, it may result in fire or explosion, do not use the battery if it is wet or damp.


- **Battery charging (for reference only):**

**Charge in the refrigerator**  
(in standby mode)




**Wall outlet AC 100~240V**  
**(using dedicated adapter)**

(For 15.6Ah battery, charging time  $\approx$  8hrs)



**Car cigarette lighter**  
**DC 12/24V**

(For 15.6Ah battery, if input voltage  
 $> 13.5V$ , charging time  $\approx$  8hrs)



**Solar**  
**12~50V**

Connect to the "SOLAR"  
port of the refrigerator

(For 15.6Ah battery, when using 100W  
solar panel, charging time  $\approx$  5hrs)



**charge separately**



**Battery charger (optional)**

Connect to the DC charging  
port of the battery  
(Charging time  $\approx$  8h)

Note: It is suggested to switch off the refrigerator when charging the battery (the power supply may mainly power the compressor when the refrigerator is running).

When connect to a solar panel, please place the refrigerator in a cool place to dissipate heat.


The charging input power should be higher than the working power of the refrigerator(about 40-45W), or switch off the refrigerator, otherwise the battery will run out.


**It is suggested to use 100W optional solar panel.**

**MAX Solar Input Voltage: 50V; MAX Solar Input Current:10A.**

Note: the output of the solar panel is unstable, so it cannot power the refrigerator directly.

When using a solar panel, the battery should be put into the refrigerator.



- **Checking Charge Status:** When the refrigerator is powered ON and DC / AC power is connected, the battery icon on display screen will flash to show charging. To charge the fridge / freezer battery without running the compressor, simply connect the adapters without powering "ON" the fridge. To view charging status please press and hold button  for 3 seconds. The fridge's battery status and voltage will be displayed. When the voltage reaches 12.6V and the battery icon stops flashing, the unit has been fully charged and wiring should be disconnected to prevent internal component from damage.


 **Warning:** Do not charge fridge / freezer with DC 12V and Solar Panel at the same time! The fridge could be seriously damaged and pose a potential hazard to you.

- **AC Charging Management**

If the fridge has not been used for a long time, the battery may be discharged, and the fridge will not power on. Please use the AC adapter to charge the fridge battery and run the fridge. After the fridge battery has charged up to 30%, you can switch to other methods for charging.


- **Car Cigarette Lighter Charging Management**

The product has a three-level battery protection function, which not only guarantees the normal operation of the product, but also protect the battery of the vehicle. When in the power-on state, long press button  for 3 seconds and the display screen flashes H, select low voltage production L(ow), M(edium), and H(igh) by clicking button . The factory default is set to H(igh) protection.



H should be set when the product is connected to car power, and M or L should be set when it is connected to a portable battery or other back-up battery. Because of the different output voltages between vehicles, the battery protection level can be set from H to M or from M to L if there is a voltage protection code F1 shown on the panel. The battery protection level should be set to H if the product will keep working after turning off the car engine, or the product may drain the battery.

- **Solar Charging Management**

To make sure your fridge is being charged by a solar panel, please turn the fridge on first. The battery icon will flash on the display screen to show the charging status. The fridge can be turned off while it is being charged. Press and hold button  for over 3 seconds to check the battery status and volatage. An extension cable may be required to keep the fridge in a cool place (to avoid overheating) while the solar panel is in the sun. Input power for charging should be higher than the refrigerator power draw (about 40-45w), otherwise the optional battery will not charge at the same time. To ensure that solar charging power is higher than refrigerator working power, a 100-Watt solar panel is advised.

## BATTERY USAGE

- **Optional Removable Battery:** The lithium battery is back up power to keep the refrigerator working for short periods while off grid.

- **Notice:** When not using the battery power or fridge for a long time, please turn off the battery output. (Hold setting button for 3 Sec).

- **Maintain Battery Charge:**

1. Home / Hotel: Use AC adapter to charge unit from AC outlet.

2. Car / Boat: Use DC port to power the fridge and charge the battery.

3. Off Grid:- Put the optional battery inside the battery compartment of the fridge, and connect the optional solar panel to the fridge . Or use portable 12V power system / solar system. Do NOT connect the solar panel directly to the battery.

- **Extended battery usage:**

1. Cool down the fridge before your journey: It is always suggested to charge fridge battery and cool the fridge down in advance with the mains to DC adapter from the wall outlet the day before the trip.

To prepare for off-grid fridge usage, place food and beverages inside fridge for cooling the day before. This will not only keep the optional battery more durable, but also save energy for outdoor activities once on battery mode.

2. Disconnecting the Battery: The battery can be removed or disconnected with the side button. This prevents the battery from discharging. The product will work from the AC adapter or car outlet without the optional battery installed. Note: Please charge fully the optional battery before it is put into storage 1 month or more.

## FOOD STORAGE








- **Freezer (-4° F~32° F)(-20°C~0°C):**

1. Meat should be cut and packed properly when placed in the fridge.
2. Do not put the fresh food and frozen food together.
3. Do not store glass containers or other containers which seal in liquid in the freezer, to avoid explosion.

- **Refrigerator (32° F~50° F)(0°C~10°C):**



1. Egg, butter, milk and bottle drinks can be stored.
2. All food should be packed appropriately before being stored in the fridge.
3. Place food in refrigerator after it gets cool in order to save energy.


- **Recommended temperature for common food:**

						
Drinks	Fruits	Vegetable	Delicatessen	Wine	Ice cream	Meat
5°C/41°F	5~8°C/41~46°F	3~10°C/37~50°F	4°C/39°F	10°C/50°F	-10°C/14°F	-18°C/0°F

## SMART CONTROL FRIDGE APP APPLICATION INSTRUCTION

### Downloading the "BRASS MONKEY FRIDGE" Application

- Using a pre-installed QR reader on your handheld smart device scan the QR code in the manual or on the carton, or search for the "BRASS MONKEY FRIDGE" APP in the iTunes App Store (for Apple devices) or Google store (Android Devices).
- Start the application and select the "Search" function.
- The application will prompt you to pair the fridge by pressing the set button  on the fridge's control panel. Once set button  has been activated, the fridge will be paired with your smart device and the application will switch to a control panel allowing you to control the fridge's functions.



**Please scan the QR code to download APP**

QR Code for Apple Devices

QR Code for Android Devices



## CLEANING & MAINTENANCE

1. Do not wash the product with water or soak.
2. Please disconnect from power before cleaning the product to avoid electrical shock.
3. Drain the product simply by removing the plug at the bottom.
4. Clean it with a soft wet cloth.

If you will not use the product for a long period of time, ensure you:

1. Turn it off and disconnect from power.
2. Remove everything from inside (food, drinks, etc)
3. Drain any remaining water by removing the drain plug, then wipe all internal surfaces with a soft cloth to ensure that they are clean and dry.
4. Keep it stored away from wet or humid places.

## TROUBLE SHOOTING

- The product is not working:
  - If using the 240V AC to 12V DC adapter check the power supply is working
  - If using the DC cable please ensure the cable still works.
  - Check the power supply is working
  - Check if the plug and socket are connected
  - Check the fuse
  - Check power switch on control panel is on
  - Compressor starts delay protection for 3 minutes after turning on
- Food inside the product is frozen:
  - Temperature is set too low
- Water flowing sound inside the tank:
  - Refrigerant is flowing, this is normal

- Water drops around the case or door gap:
  - When moisture in the air meets the lower temperature case, it will naturally become liquefied and condensed. Wipe away with a towel or soft cloth
- Code F1 displayed:
  - Low voltage protection, which can be solved by setting the battery protection button from H to M or from M to L
- Code F2 displayed:
  - Fan overload protection. Please turn off the product and restart it after 30 minutes. If the code displays again, please contact the place of purchase
- Code F3 displayed:
  - Compressor frequent start protection. Please turn off the product and restart it after 30 minutes. If the code displays again, please contact the place of purchase
- Code F4 displayed:
  - Compressor is overloaded or working at a low speed. Please turn off the product and restart it after 30 minutes. If the code displays again, please contact the place of purchase
- Code F5 displayed:
  - High temperature compressor module protection. Please move the product to a ventilated area and turn it off for 30 minutes then restart it. If the code displays again, please contact the place of purchase
- Code F6 displayed:
  - No parameter can be detected by the controller. Please restart the product. If the code displays again, please contact the place of purchase
- Code F7 / F8 displayed:
  - Temperature sensor error protection. Please check the sensor terminal

The warranty for this product is 3 years from date of purchase. During the warranty period the following are excluded from coverage:

- Intentional damage
- Damage by fire, flood, etc
- Damage or malfunction caused by incorrect usage and not following this user manual
- Damage or malfunction caused by disassembling



