

**Model**  
**Production**

**QM1321**  
**Auto Range Digital Multimeter**

	Range	Accuracy
DC Voltage	40mV/400mV/4V/40V/400V/1000V	±(0.5%+3)
AC Voltage	40mV/400mV/4V/40V/400V/750V	±(0.8%+5)
DC Current	400μA/4000μA/40mA/400mA/4A/10A	±(1.0%+5)
AC Current	400μA/4mA/40mA/400mA/4A/10A	±(1.5%+5)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(0.8%+5)
Capacitance	10nF/100nF/1μF/10μF/100μF/1mF/10mF/100mF	±(4.0%+15)
Frequency	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz	±(0.5%+2)

Max. Display	4000 counts
True RMS	Yes
Transistor hFE Test	0 ~ 1000
Duty Cycle	1% ~ 99%
Diode Test	Yes
Continuity Check	Yes
NCV	≥ AC 65~600Vrms
LINE Test	Live Wire Recognition
Sampling Rate	approx 2/s
Max. Input Protection	1000V
Max./Min. Hold	Yes
LCD Backlight	Yes
Relativity (Zero)	Yes
Auto Power Off	Yes
Auto Power Off Disable	Yes

Max Input Voltage	750VAC RMS, 1000VDC
Operating Temperature	0°C-40°C
Operating Humidity	<80%RH
Storage Temperature	-10°C-60°C
Storage Humidity	<70%RH
Power Supply	9V Battery (6F22)
Product Size (mm)	200x92x60 mm
Product Weight (g)	Approx.230g (including battery)
Safety Rating	CAT III 1000V