



SL3742

2000LM 2-in-1 LED Torch & Work Light



INSTRUCTION MANUAL

INTRODUCTION

- The product features a combined structure of increased safety, intrinsic safety, and encapsulation protection types.
- The increased safety chamber consists of the power housing, power cover, cover plate, and related components, containing the power supply and terminal blocks.
- The lamp and main control board are of an integral encapsulated structure.
- The switch is intrinsically safe.
- The product is powered by two 21700 4500mAh batteries.

OPERATING INSTRUCTIONS

Warning: It is strictly prohibited to disassemble, charge, or replace the battery in hazardous areas.


The explosion-proof work light can operate reliably under the following conditions:

- Altitude not exceeding 2000 m, atmospheric pressure: 80–110 kPa
- Ambient temperature: -20°C to +40°C
- Relative humidity of surrounding air not exceeding 95% (+25°C)
- In locations without dripping water or liquid ingress
- Pollution degree: Level 3
- Installation category: Class III

BOX CONTENTS

- Product instruction manual
- USB charging cable

PRODUCT OVERVIEW



1. Digital power display
2. Side light
3. Front light
4. Type-C charging port
5. Toggle switch
6. Power switch

INSTALLATION AND USE PRECAUTIONS

Charging

Connect the supplied charger to the charging port on the product.

During charging, the digital display will show a lightning icon.

When the battery is fully charged, the digital display will indicate 100% battery level.

Power Switch

Press and hold Switch 1 or Switch 2 for approximately 2 seconds to turn the product ON or OFF.

Mode Selection

Front Light Modes

Short press Switch 1 to cycle through the following modes:

High Brightness / Medium Brightness / Low Brightness / Flashing Mode

Side Light Modes

Short press Switch 2 to cycle through the following modes:

- White High Brightness
- White Low Brightness
- Yellow High Brightness
- Yellow Low Brightness
- White and Yellow Simultaneous Mode

Stand Usage

The product is equipped with an adjustable stand on the bottom, allowing the lighting angle to be adjusted as required.

Extend and position the stand to the desired angle and secure it in place.

SPECIFICATIONS

LEDs: 3 x P70 LEDs + 2 x COB (High Intensity LEDs)

Battery: 2 x 21700 / 4500mAh

Brightness: Front LED 2000 lumens + Side Light 1000 lumens

Charging Time: 3-4 hours

Working Time: 7-8 hours

Material: PC + TPR

WARRANTY INFORMATION

Our product is guaranteed to be free from manufacturing defects for a period of 12 Months.

If your product becomes defective during this period, Electus Distribution will repair, replace, or refund where a product is faulty; or not fit for intended purpose.

This warranty will not cover modified product; misuse or abuse of the product contrary to user instructions or packaging label; change of mind and normal wear and tear.

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and failure does not amount to a major failure.

To claim warranty, please contact the place of purchase. You will need to show receipt or other proof of purchase. Additional information may be required to process your claim.

Any expenses relating to the return of your product to the store will normally have to be paid by you.

The benefits to the customer given by this warranty are in addition to other rights and remedies of the Australian Consumer Law in relation to the goods or services to which this warranty relates.

This warranty is provided by:

Electus Distribution

Address 46 Eastern Creek Drive, Eastern Creek NSW 2766

Ph. 1300 738 555